



Image is for illustrative purposes only © F.E.D.

FAGOR EVO-ADVANCE PASS-THROUGH DISHWASHER WITH DRAIN PUMP AD-125HRS

Hood type dishwasher - EVO Generation - Advance range.
Fagor EVO-ADVANCE pass-through dishwasher with drain pump, detergent and rinse dispenser and HRS

DESCRIPTION

Fagor EVO-ADVANCE pass-through dishwasher with drain pump, detergent and rinse dispenser and HRS AD-125HRS

HIGH TECHNOLOGY WITHIN EVERYONE'S REACH.

For those who believe that technology and simplicity can go hand-in-hand, the E-VO CONCEPT has arrived. Versions

Hood type dishwasher - EVO Generation - Advance range.

Hourly production: 65 baskets/hour - 1170 dishes/hour.

Clearance (max ware height): 440 mm.

Wash cycles: 55"- 90" - 120".

GLASS cycle: special program for washing glassware, based on the specifications of hygiene and safety standard DIN 10511. Cycle of 90 seconds, with temperatures: 60 °C (wash) and 65 °C (rinse).

HRS: version with energy recuperator. HRS collects and condenses the steam exhausted by the machine after a full cleaning cycle, and heats up the input water. Power: 30 W.

Made of stainless steel. Includes double skin insulated hood, external, front and side panels.

Full double skin body and hood to isolate machine's noise from the environment.

Counterbalanced hood.

Double rotating wash and rinse systems made of stainless steel, above and below.

Tray filters on the tank, made of AISI-304 stainless steel.

Two wash pumps, 600 W each.

Rinsing pump: 260 W. Air break system.

Drain pump: 70 W. Drainage cycle.

Tank with 1.8 kW heating element.

Tank capacity: 28 litres.

Boiler with multipower heating elements: 3 / 4,5 / 6 / 9 kW.

Boiler capacity: 9 litres.

Water consumption: 2.4 litres/rinse.

Thermostatic temperature control: washing at 60°C and rinsing at 90°C.

Thermo stop system that guarantees minimum rinsing temperature of 85°C.

Safety thermostats.

Built-in automatic rinse dispenser and detergent doser.

Safety magnetic switch for hood opening.

Adjustable legs.

Water protection rating: IPX5

Total power: adjustable: 4,2 ÷ 12,0 kW.

Dimensions: 658 x 756 x 1540 mm.

Height with HRS recuperator: 2.200 mm.

Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 8 cutlery containers.

SPECIFICATIONS

NET WEIGHT (KG)	160
WIDTH (MM)	658
DEPTH (MM)	756
HEIGHT (MM)	2258
PACKING WIDTH (MM)	700
PACKING DEPTH (MM)	840
PACKING HEIGHT (MM)	2040
POWER	adjustable: 4,2 ÷ 12,0 kW.